



IPH Series PUMP LTD

4.331 Inch | 110 Millimeter x 3.543 Inch | 90 Millimeter x 5.63 Inch | 143 Millimeter TIMKEN LSM110BRHSATL Pillow Block Bearings



LSM110BRHSATL Bearing 2D drawings and 3D CAD models

Bearing No. LSM110BRHSATL

| | |
|---------------------------|--|
| Category | Pillow Block Bearings |
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 38.59 |
| EAN | 0013992044556 |
| Product Group | B04144 |
| Number of Mounting Holes | 2 |
| Mounting Method | Clamp Collar |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Cylindrical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-Expansion |
| Mounting Bolts | 24 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | LSM110BR |
| Seals | Triple Lip Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch - Metric | Metric |
| Other Features | Single Row Light Duty With Support Wide Inner Ring |
| Category | Pillow Block Bearings |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| | |



IPH Series PUMP LTD

| Noun | Bearing |
|-------------------------------|---|
| Keyword String | Pillow Block |
| Manufacturer URL | http://www.timken.com |
| Weight / LBS | 85 |
| Nominal Bolt Center to Center | 15.4 Inch 392 Millimeter |
| Bolt Spacing Minimum | 0 Inch 0Millimeter |
| B | 5.63 Inch 143 Millimeter |
| D | 3.543 Inch 90 Millimeter |
| d | 4.331 Inch 110 Millimeter |
| Bolt Spacing Maximum | 0 Inch 0Millimeter |
| Actual Bolt Center to Center | 15.4 Inch 392Millimeter |
| Shaft Size | 110 mm |
| Seal Type | Aluminium Triple Labyrinth |
| Bearing Type | Split Cylindrical Retained Type |
| Support Type | Two-Bolt Plummer Block |
| Series Type | Light Series |
| Pillow/Plummer Block Style | Split Cylindrical Housed Unit - Standard |
| Bolt Size | 2 x M24 |
| Weight | 111 lb |
| Dimension H | 5.630 in |
| Dimension H1 | 2.4 in |
| Dimension H2 | 12.4 in |
| Dimension J | 15.4 in |
| Dimension L | 18.3 in |
| Dimension M | 4.7 in |
| Housing Width | 5.6 in |
| Cr - Dynamic Load Rating | 71040 lbf |
| Cor - Static Load Rating | 95993 lbf |
| Ca - Axial Load Rating | 4181.39 lbf |



IPH Series PUMP LTD

| | |
|---------------|--|
| Maximum Speed | 1970 rpm |
| Note | This product line was formerly known as "Revolvo " |